

45 Series Medium Duty Casters



Features:

Swivel Section: Cold-forged top plate, yoke and button are all heat treated to prevent brinelling, improve swivel action and increase service life.

Axle: 1/2" Diameter with lubrication fitting.

Finish: Corrosion resistant zinc.

Wheel Bearings: Straight roller bearings standard.

Top Plate:

| Mounting Plate | Bolt Hole Spacing | Bolt Size |
|----------------|--------------------------------------|-----------|
| 4 x 4-1/2 | 2-5/8 x 3-5/8 slotted to 3 x 3 | 3/8 |

Options:

CB: Cam Brake

Capacity to 900 lbs.

4 - 8 Inch Wheels



| Diameter Inches | Width Inches | Wheel Type | Bearing Type | Capacity Pounds | Overall Ht. Inches | Swivel Model No. | Rigid Model No. |
|-----------------|--------------|----------------------|--------------|-----------------|--------------------|------------------|-----------------|
| 4 | 2 | Cast Iron | Roller | 700 | 5-5/8 | 45CIR42S | 45CIR42R |
| | | Phenolic | Roller | 700 | | 45PNR42S | 45PNR42R |
| | | Polyolefin | Roller | 400 | | 45POR42S | 45POR42R |
| | | Polyurethane on Iron | Roller | 700 | | 45PIR42S | 45PIR42R |
| | | Rubber on Iron | Roller | 350 | | 45RIR42S | 45RIR42R |
| 5 | 2 | Cast Iron | Roller | 900 | 6-1/2 | 45CIR52S | 45CIR52R |
| | | Phenolic | Roller | 900 | | 45PNR52S | 45PNR52R |
| | | Polyolefin | Roller | 500 | | 45POR52S | 45POR52R |
| | | Polyurethane on Iron | Roller | 900 | | 45PIR52S | 45PIR52R |
| | | Rubber on Iron | Roller | 400 | | 45RIR52S | 45RIR52R |
| 6 | 2 | Cast Iron | Roller | 900 | 7-1/2 | 45CIR62S | 45CIR62R |
| | | Phenolic | Roller | 900 | | 45PNR62S | 45PNR62R |
| | | Polyolefin | Roller | 700 | | 45POR62S | 45POR62R |
| | | Polyurethane on Iron | Roller | 900 | | 45PIR62S | 45PIR62R |
| | | Rubber on Iron | Roller | 450 | | 45RIR62S | 45RIR62R |
| 8 | 2 | Cast Iron | Roller | 900 | 9-1/2 | 45CIR82S | 45CIR82R |
| | | Phenolic | Roller | 900 | | 45PNR82S | 45PNR82R |
| | | Polyolefin | Roller | 800 | | 45POR82S | 45POR82R |
| | | Polyurethane on Iron | Roller | 900 | | 45PIR82S | 45PIR82R |
| | | Rubber on Iron | Roller | 500 | | 45RIR82S | 45RIR82R |

NASCO-OP™
Power of Numbers
800-321-3396