



ARMOR GUYS
• PROTECTED •

EXTRAFLEX

HCT
HCT
Hybrid Coating Technology

04-001 SPECIFICATION SHEET

FEATURES:

FIBER
15'G Gray Nylon Liner

COATING
HCT Black Nitrile Microfoam
Palm Coating

BENEFITS:

"All in one" : Fit, Feel, Flexibility, Breathability, Durability
Excellent wet grip

CATEGORY:

Extraflex

APPLICATIONS:

- Aerospace
- Appliance Manufacturing
- Automotive
- General Carpentry
- Micro-engineering
- Lumber/Wood/Paper
- Metal Fabrication
- Metalworking
- Plastics
- Plumbers

Armor guys reference number : 04-001

CARE INSTRUCTIONS:

Recommended washing temperature is between 40°C and 60°C (104 - 140°F) with mild detergents.

The drying process may cause felting on the fabric surface.
Drying temperatures should not exceed 70°C (158°F)



CE

EN388



4121



Tested for harmful substances according to Oeko-Tex® Standard 100 SH40098266 TESTEX

SPECIFICATIONS

MATERIALS	Spandex Nylon liner
COLOR	Gray
WRIST DESIGN	Continuous Knit
SIZES	XS -XXL

PACKAGING						
CASE SIZE	XS	S	M	L	XL	XXL
PER CARTON	120	120	120	120	120	120
CUFF COLOR	Purple	Red	Yellow	Brown	Black	Light Blue
ORIGIN	PRC					

PERFORMANCE LEVEL

EN388: 4121						
ABRASION	0	1	2	3	4	5
CUT	0	1	2	3	4	5
TEAR	0	1	2	3	4	5
PUNCTURE	0	1	2	3	4	5



800.321.3396
www.nascoop.com