

· PROTECTED ·



SPECIFICATIONS

| COATING MATERIALS | Green Nitrile Coating | | |
|-------------------|-----------------------|--|--|
| SIZES | XS-XXL | | |

PACKAGING

| CASE SIZE | XS | S | М | L | XL | XXL | | |
|--------------------|-----------|-----------|-----------|-----------|-----------|---------------|--|--|
| PER CARTON | 144 | 144 | 144 | 144 | 144 | 144 | | |
| CASE WEIGHT | 17.40/lbs | 18.06/lbs | 18.72/lbs | 19.82/lbs | 20.93/lbs | 21.59/lbs | | |
| CUFF COLOR | Purple | Red | Yellow | Brown | Black | Light Blue | | |
| ORIGIN | PRC | | | | | | | |

PERFORMANCE LEVEL

EN388: 3101

| ABRASION | 0 | 1 | 2 | 3 | 4 | 5 |
|----------|---|---|---|---|---|---|
| СИТ | 0 | | 2 | 3 | 4 | 5 |
| TEAR | 0 | 1 | 2 | 3 | 4 | 5 |
| PUNCTURE | 0 | 1 | 2 | 3 | 4 | 5 |

CHEMIFLEX



05-003 SPECIFICATION SHEET

FEATURES:

LINER 15 MIL, Flocked Liner Unsupported **COATING** Green Nitrile Coating

BENEFITS:

Excellent Solvent Resistance

RANGE:

Chemiflex

APPLICATIONS:

Chemical Processing Food Processing Machining Printing Press Operations Oil & Gas Petrochemicals

Armor Guys reference number: 05-003

CARE INSTRUCTIONS:

Recommended washing temperature is between 40° C and 60° C (104 - 140°F) with mild detergent.

The drying process may cause felting on the fabric surface. Drying temperatures should not exceed $70^{\circ}C$ (158°F)



800.321.3396 www.nascoop.com