



WIRE & CABLE STRIPPERS

Deltax

DEL-CSX-2010-1PH DEL-CSX-2010-3PH

Strips insulation from copper or aluminum wires producing a clean, upgraded product. This unit has a capacity from 1/16" through 4-1/2" diameter wires and can process up to 110 ft. per minute. Dual cutting areas to accommodate a wide range of insulation thickness and cable diameters. 3HP - 1 or 3 phase electric motor in 220/440VAC. Overall dimensions 47"H x 30"L x 29"W, 780lbs.



DEL-CSX-001

Strips insulation from copper or aluminum wires producing a clean, upgraded product. This unit has a capacity from 1/16" through 2-3/8" diameter wires and can process up to 60 ft. per minute. Compact design for bench mounting. Close-coupled, heavy-duty gearbox and motor features one hand adjustment. 3/4HP - 1 phase electric motor in 110VAC. Overall dimensions 19"H x 13.25"L x 13"W, 90 lbs.

DEL-CSX-2000-1PH DEL-CSX-2000-3PH

Strips insulation from copper or aluminum wires producing a clean upgraded product. This unit has a capacity from 1/16" through 4" diameter wires and can process up to 72 ft per minute. Compact design for bench mounting. Close coupled heavy duty gearbox and unique roller guide feed system with fast, simple size adjustment.. 2HP - 1 or 3 phase electric motor in 220/440VAC. Overall dimensions 18-7/8"H x 17-3/4"L x 15-3/8"W, 172 lbs.



DEL-CSX-170-3PH

Oversized feed rollers with teeth, quenched and tempered and designed for intensive work with steel-armored cables. Two sets of slitter knives for top and bottom cutting and slitting of small to large common wire. Supplied with emergency safety braking system, guards, working table and full adjustments for cable size. Supplied with electrical starting panel with overload protection, forward and reverse controls. Equipped with 4HP motor with "oversized" gearbox 350 lbs/ft. of torque. Wire capacity: 1/8" to 3" at approximately 89 ft. per minute. 220/440VAC, 3ph, 60HZ. 40"L x 25"W x 50"H, 1320 lbs.



DEL-CSX-300-3PH

Oversized feed rollers with teeth, quenched and tempered and designed for intensive work with copper, lead and steel armored cables. Supplied with emergency safety braking system, guards, working table and full adjustments for cable size. Supplied with electrical starting panel with overload protection, forward and reverse controls. Equipped with 5.5HP motor with "oversized" gearbox 740 lbs/ft. of immense torque. Wire capacity: 5/8" to 4-3/4" at approximately 65 ft. per minute. 220/440VAC, 3ph, 60HZ. 59"L x 35.5"W x 62"H, 1980 lbs.



MODEL	CABLE CAPACITY (IN)	SPEED (F PM)	HP	WEIGHT (LBS)
DEL-CSX-001	1/16" thru 2-3/8"	60	3/4-1ph	90
DEL-CSX-2000	1/16" thru 4"	72	2-1ph & 2-3ph	172
DEL-CSX-2010	1/16" thru 4-1/2"	110	3-1ph & 3-3ph	780
DEL-CSX-170	1/8" thru 3"	89	4-3ph	1320
DEL-CSX-300	5/8" thru 4-3/4"	65	5.5-3ph	1980

Information displayed is for reference purposes only and is based on data provided by equipment manufacturers or distributors. Manufacturers may change specifications and consumers are to confirm the most recent information before finalizing a purchase.

800.321.3396 • www.nascoop.com

