



# Deltax

## ALLIGATOR SHEARS



**DEL-DTX-200**

Hydraulic alligator shear with 8" long blade generates 40 tons maximum cutting force at the throat. Shearing capacity of 1" diameter round mild steel. 5HP 220/440VAC three phase electric motor. Includes safety guard and adjustable hold down. Approximately 600lbs. \*\*Machine is shipped with enough fluid for it to operate properly.



**DEL-DTX-300**

Hydraulic alligator shear with 12" long blade generates 97 tons maximum cutting force at the throat. Shearing capacity of 1-3/4" diameter round mild steel. 10HP 220/440VAC three phase electric motor. Includes safety guard and manual hold down. Approximately 1850lbs. \*\*Machine is shipped with enough fluid for it to operate properly.



**DEL-DTX-400**

Hydraulic alligator shear with 16" long blade generates 117 tons maximum cutting force at the throat. Shearing capacity of 1-3/4" diameter round mild steel. 10HP 220/440VAC three phase electric motor. Includes safety guard and manual hold down. Approximately 2100lbs. \*\*Machine is shipped with enough fluid for it to operate properly.



**DEL-DTX-410**

Hydraulic alligator shear with 16" long blade generates 110 tons maximum cutting force at the throat. Shearing capacity of 1-3/4" diameter round mild steel. 10HP 220/440VAC three phase electric motor. Includes safety guard and automatic hydraulic hold down. Approximately 2300lbs. \*\*Machine is shipped with enough fluid for it to operate properly.



# Deltax



**DEL-DTX-4-600**

Hydraulic alligator shear with 24" long blade generates 120 tons maximum cutting force at the throat. Shearing capacity of 2" diameter round mild steel. 10HP 220/440VAC three phase electric motor. Includes safety guard and manual hold down. Approximately 2650lbs. \*\*Machine is shipped with enough fluid (Oil; NUTO H 46) for it to operate properly.



**DEL-DTX-600**

Hydraulic alligator shear with 24" long blade generates 200 tons maximum cutting force at the throat. Shearing capacity of 2-3/4" diameter round mild steel. 15HP 220/440VAC three phase electric motor. Includes safety guard and hydraulic hold down. Approximately 4800lbs. \*\*Machine is shipped with enough fluid (Oil; NUTO H 46) for it to operate properly.

| MODEL          | BLADE LENGTH | HP | MAX CUTTING FORCE (TONS) | CUTTING CAPACITY MILD STEEL ROUNDS (IN) | STROKES/ MINUTE | HOLD DOWN | WEIGHT (LBS) |
|----------------|--------------|----|--------------------------|-----------------------------------------|-----------------|-----------|--------------|
| DEL-DTX-200*   | 8"           | 5  | 40                       | 1"                                      | 20-60           | Manual    | 600          |
| DEL-DTX-300*   | 12"          | 10 | 97                       | 1-3/4"                                  | 12-60           | Manual    | 1850         |
| DEL-DTX-310*   | 12"          | 10 | 90                       | 1-3/4"                                  | 16-60           | Hydraulic | 2050         |
| DEL-DTX-300RB* | 12"          | 10 | 120                      | 2"                                      | 11-50           | Hydraulic | 2400         |
| DEL-DTX-340*   | 14"          | 5  | 45                       | 1-1/4"                                  | 16-60           | Manual    | 1045         |
| DEL-DTX-400*   | 16"          | 10 | 117                      | 1-3/4"                                  | 12-60           | Manual    | 2100         |
| DEL-DTX-410*   | 16"          | 10 | 110                      | 1-3/4"                                  | 14-60           | Hydraulic | 2300         |
| DEL-DTX-4/600* | 24"          | 10 | 120                      | 2"                                      | 14-60           | Manual    | 2650         |
| DEL-DTX-4/610* | 24"          | 10 | 120                      | 2"                                      | 14-60           | Hydraulic | 2850         |
| DEL-DTX-600    | 24"          | 15 | 200                      | 2-3/4"                                  | 14-50           | Hydraulic | 4800         |

\*Available in 220VAC-1ph and 220/440VAC-3ph

*Information displayed is for reference purposes only and is based on data provided by equipment manufacturers or distributors. Manufacturers may change specifications and consumers are to confirm the most recent information before finalizing a purchase.*

