



# Deltax

## ALLIGATOR SHEARS



**DEL-DTX-200**

Hydraulic alligator shear with 8" long blade generates 40 tons maximum cutting force at the throat. Shearing capacity of 1" diameter round mild steel. 5HP 220/440VAC three phase electric motor. Includes safety guard and adjustable hold down. Approximately 600lbs. \*\*Machine is shipped with enough fluid for it to operate properly.



**DEL-DTX-300**

Hydraulic alligator shear with 12" long blade generates 97 tons maximum cutting force at the throat. Shearing capacity of 1-3/4" diameter round mild steel. 10HP 220/440VAC three phase electric motor. Includes safety guard and manual hold down. Approximately 1850lbs. \*\*Machine is shipped with enough fluid for it to operate properly.



**DEL-DTX-400**

Hydraulic alligator shear with 16" long blade generates 117 tons maximum cutting force at the throat. Shearing capacity of 1-3/4" diameter round mild steel. 10HP 220/440VAC three phase electric motor. Includes safety guard and manual hold down. Approximately 2100lbs. \*\*Machine is shipped with enough fluid for it to operate properly.



**DEL-DTX-410**

Hydraulic alligator shear with 16" long blade generates 110 tons maximum cutting force at the throat. Shearing capacity of 1-3/4" diameter round mild steel. 10HP 220/440VAC three phase electric motor. Includes safety guard and automatic hydraulic hold down. Approximately 2300lbs. \*\*Machine is shipped with enough fluid for it to operate properly.



# Deltax



**DEL-DTX-4-600**

Hydraulic alligator shear with 24" long blade generates 120 tons maximum cutting force at the throat. Shearing capacity of 2" diameter round mild steel. 10HP 220/440VAC three phase electric motor. Includes safety guard and manual hold down. Approximately 2650lbs. \*\*Machine is shipped with enough fluid (Oil; NUTO H 46) for it to operate properly.



**DEL-DTX-600**

Hydraulic alligator shear with 24" long blade generates 200 tons maximum cutting force at the throat. Shearing capacity of 2-3/4" diameter round mild steel. 15HP 220/440VAC three phase electric motor. Includes safety guard and hydraulic hold down. Approximately 4800lbs. \*\*Machine is shipped with enough fluid (Oil; NUTO H 46) for it to operate properly.

MODEL	BLADE LENGTH	HP	MAX CUTTING FORCE (TONS)	CUTTING CAPACITY MILD STEEL ROUNDS (IN)	STROKES/ MINUTE	HOLD DOWN	WEIGHT (LBS)
DEL-DTX-200*	8"	5	40	1"	20-60	Manual	600
DEL-DTX-300*	12"	10	97	1-3/4"	12-60	Manual	1850
DEL-DTX-310*	12"	10	90	1-3/4"	16-60	Hydraulic	2050
DEL-DTX-300RB*	12"	10	120	2"	11-50	Hydraulic	2400
DEL-DTX-340*	14"	5	45	1-1/4"	16-60	Manual	1045
DEL-DTX-400*	16"	10	117	1-3/4"	12-60	Manual	2100
DEL-DTX-410*	16"	10	110	1-3/4"	14-60	Hydraulic	2300
DEL-DTX-4/600*	24"	10	120	2"	14-60	Manual	2650
DEL-DTX-4/610*	24"	10	120	2"	14-60	Hydraulic	2850
DEL-DTX-600	24"	15	200	2-3/4"	14-50	Hydraulic	4800

\*Available in 220VAC-1ph and 220/440VAC-3ph

*Information displayed is for reference purposes only and is based on data provided by equipment manufacturers or distributors. Manufacturers may change specifications and consumers are to confirm the most recent information before finalizing a purchase.*

