



WIRE & CABLE STRIPPERS

GENSCO

GEN-CS-115-3PH GEN-CS-115-1PH

Strips insulation from copper or aluminum wires producing a clean upgraded product. This unit has a capacity from 1/16" through 4-1/2" diameter wires and can process up to 110 ft per minute. Dual cutting areas to accommodate a wide range of insulation thickness and cable diameters. 3HP - 1 or 3 phase electric motor in 220/440VAC. Overall dimensions 50"H x 40"L x 25"W, 1320 lbs.



GEN-CS-60

Strips insulation from copper or aluminum wires producing a clean, upgraded product. This unit has a capacity from 1/16" through 2-3/8" diameter wires and can process up to 60 ft. per minute. Compact design for bench mounting. Close-coupled, heavy-duty gearbox and motor features one hand adjustment. 3/4HP - 1 phase electric motor in 110VAC. Overall dimensions 19"H x 13.25"L x 13"W, 90 lbs.

GEN-CS-85

Strips insulation from copper or aluminum wires producing a clean upgraded product. This unit has a capacity from 1/16" through 3-3/8" diameter wires and can process up to 110 ft per minute. Compact design for bench mounting. Close coupled heavy duty gearbox and motor. 1.5HP - 1 phase electric motor in 220VAC. Overall dimensions 18-7/8"H x 17-1/4"L x 15-3/8"W, 140 lbs.



GEN-W-170-3PH

Oversized feed rollers with teeth quenched and tempered and designed for intensive work with steel armored cables. Two sets of slitter knives for top and bottom cutting and slitting of small to large common wire. Supplied with emergency safety braking system, guards, working table and full adjustments for cable size. Supplied with electrical starting panel with overload protection, forward and reverse controls. Equipped with 4HP motor with "oversized" gearbox 350lbs/ft of torque. Wire capacity: 1/8" to 3" at approximately 89ft per minute. 220/440V, 3ph, 60HZ. 56"L x 36"W x 50"H. 1500lbs.



GEN-W-300-3PH

Oversized feed rollers with teeth, quenched and tempered and designed for intensive work with copper, lead and steel armored cables. Supplied with emergency safety braking system, guards, working table and full adjustments for cable size. Supplied with electrical starting panel with overload protection, forward and reverse controls. Equipped with 5.5HP motor with "oversized" gearbox 740lbs/ft of immense torque. Wire capacity: 5/8" to 4-3/4" at approximately 65 ft. per minute. 220/440V, 3ph, 60HZ. 61"L x 36"W x 60"H. 2100lbs.



MODEL	CABLE CAPACITY (IN)	SPEED (F PM)	HP	WEIGHT (LBS)
GEN-CS-60	1/16" thru 2 3/8"	60	3/4-1ph	90
GEN-CS-115-3PH	1/16" thru 4 1/2"	72	2-1ph & 2-3ph	1320
GEN-CS-115-1PH	1/16" thru 4 1/2"	110	3-1ph & 3-3ph	1320
GEN-W-170-3PH	1/8" thru 3"	89	4-3ph	1500
GEN-W-300-3PH	5/8" thru 4 3/4"	65	5.5-3ph	2100



800.321.3396
nascoop.com

