



Exclusive, vented Type II AccuFlow™ manifold with a Safe-Squeeze® trigger handle provides the fastest, smoothest, most controlled pouring

NEW



Flexible 9" (229 mm) hose, offers targeted pouring into small openings



Quick-fill port on Type II AccuFlow™ features an ergonomically designed lift lever that opens wide for easy filling

NEW



Extra capacity in all cans accommodates oil additives for two cycle engines



Half-inch (13mm) grip lip along bottom supports pouring and resists accidental punctures when placed on uneven surfaces



Stainless Steel flame arrester stops flashback ignition, provides faster liquid flow, and offers superior chemical and corrosion resistance. Long 3-1/2" (88mm) length for safe secure insertion of gas nozzle

NEW



Optional 2-position polypropylene funnel for Type I cans aids in pouring and folds down for compact storage and filling



Large ID zone permits user labeling to avoid misuse, mishaps with incompatible mixtures, or to identify owner or department

NEW



Comfortable, rounded handle doesn't cut into hand

Leakproof, positive pressure relief lid automatically vents to prevent rupture or explosion. It is spring-loaded to self-close controlling vapors and spills

100% leak tested and fully compliant

Trilingual warning label

Free swinging handle with counter-balanced design leverages the weight of the can against the opening mechanism for easy pouring and carrying

100% steel body and handle constructed of 24-gauge galvanized steel finished in an environmentally friendly, tough powder paint that resists solvents and stands up to abuse

Reinforcing ribs strengthen walls and reduce denting

Double lock seams at base & top offer four thicknesses of steel for extra "bumper guard" protection

Exclusive 10-year limited warranty

Type I

