

# POWERTRAX



**SMOOTH**



**LUG**

## SKID STEER

Reinforced sidewalls and beads for enhanced lateral stability  
 Extra Heavy Duty—Premium natural rubber compound

TIRE AND WHEEL ASSEMBLY OR TIRE ONLY

| PRODUCT# | DESCRIPTION     | OVERALL DIA. | SECT. WIDTH | TREAD DEPTH | WEIGHT | MAX LOAD (16 MPH) |
|----------|-----------------|--------------|-------------|-------------|--------|-------------------|
| 22380B00 | 10-16.5 SMOOTH  | 30           | 10          | N/A         | 155    | 6600              |
| 22380BW0 | 10-16.5 TWA SM  | 30           | 10          | N/A         | 254    | 6600              |
| 22560B00 | 12-16.5 SMOOTH  | 33           | 10 3/4      | N/A         | 216    | 8800              |
| 22560BW0 | 12-16.5 TWA SM  | 33           | 10 3/4      | N/A         | 328    | 8800              |
| 22380B01 | 10-16.5 LUG     | 30           | 10          | 1 1/2       | 144    | 6600              |
| 22380BW1 | 10-16.5 TWA LUG | 30           | 10          | 1 1/2       | 248    | 6600              |
| 22560B01 | 12-16.5 LUG     | 33           | 10 3/4      | 1 1/2       | 216    | 8800              |
| 22560BW1 | 12-16.5 TWA LUG | 33           | 10 3/4      | 1 1/2       | 320    | 8800              |



**800-321-3396**

# **PowerTrax: Skid-Steer Solids**

## **8 Hole Models**

|             |  |
|-------------|--|
| Bobcat      | S-150,300,700-800 Series                 |
| Case        | 1845C                                    |
| Cat         | 216-226-246                              |
| Gehl        | SL-4635 5000-6000 Series                 |
| John Deere  | 260-270-325                              |
| Mustang     | 960-2060-2070                            |
| New Holland | 785-885 LS-160, LS-170<br>LX-160, LX-170 |