

# GENERAL SERVICE SOLID EF CLIP



Built in lock ring for easy mounting. Same quality and construction as a GSS pneumatic shaped solid.

PRODUCT #	SIZE	RIM WIDTH	OD + OR - 2%	SECTION WIDTH	LOAD 6 MPH	WT
24904131	15x4 1/2x8	3	14 1/2	4 1/4	1890	20
24904101	15x4-1/2x8	3	14 1/2	4 1/4	1890	20
24905131	15x4 1/2x8	3 1/4	14 7/8	4	1890	20
24910131	16x6-8	4.33	15 1/2	6	2780	33
24915131	18x7-8	4.33	17 1/2	6 1/2	4695	46
24218131	500x8	3	17 3/4	5	2400	36
24300131	600x9	4	20	5 1/2	4210	58
24925131	21x8-9	6	20	7	6190	70
24330131	650x10	5	22 1/2	6	5800	79
24845131	200x50-10	6 1/2	17	7 1/2	5400	53
24930131	23x9-10	6 1/2	22	7 3/4	7525	99
24400131	700x12	5	25 3/4	6 1/4	6640	100
24935131	23x10-12	8	22 3/4	9 1/4	8820	116
24940131	27x10-12	8	26	9 1/2	8400	165
24410131	700x15 (29x8x15)	5 1/2	28	7	7850	127
24510101	750x15	5.5	29 1/8	7 1/2	8400	150
24580131	815x15 (28x9x15)	7	26 1/4	7 1/2	9100	130
24610131	825x15	6 1/2	31 1/4	7 3/4	10880	187
24950131	250x15	7	27 1/4	9	9615	146
24952131	250x15	7 1/2	28	9	9615	146
24955131	300x15	8	32	11	13190	238
24835131	28x12.5-15	9 3/4	27	11	12850	196

**N**ote: Welded lugs or fins on wheels cause structural damage to pneumatic shaped solid tires with steel reinforced base. Mounting these tires on welded lug or finned wheels voids the warranty.



800-321-3396