

LASERLIGHT 2

REMOTE DISPLAY



800-321-3396

www.nascoop.com

LASERLIGHT2

REMOTE DISPLAY



Bright and Vivid Display, Even in Direct Sunlight

Prominently display weight, numeric data and messages with the LaserLight2 remote display. A super-bright LED display with non-glare lens provides sharp seven-segment, six-digit characters that are easy to read. Never lose visibility in dark conditions or experience wash-out in direct sunlight. Simply power up a LaserLight2 remote display in your application and the benefit are clearly visible.



Stop/Go Model

A redesigned enclosure provides easy access to internal components. The front panel swings open for convenient setup and service, yet is securely held in place. The weather-tight, IP66 rated enclosure provides superior protection for worry-free daily use. The external keypad makes navigating configuration options safe and easy with up, down, left and right arrow keys as well as Enter, Setup, Mode, Set and Learn buttons.

Available in four-inch or six-inch character sizes, LaserLight2 remote displays include annunciators for gross, net, pounds, and kilograms. For added convenience, time and date is also included.

To simplify installation and make retrofitting an attractive option, Auto Learn mode identifies communication formats and data rates used by existing weight indicators. Use LaserLight2 with virtually any weight indicator and you'll experience a seamless installation every time.

Mounting options include a flange tab which accommodates 1/4-inch hardware for vertical surface or pole mounting, or VESA mounting bracket for increased versatility. With the VESA mount, a wide variety of readily available mounting options typically used for flat-panel TVs are compatible with the LaserLight2.



The LaserLight2 remote display—providing crisp, accurate weight readings in any condition to ensure your process is always in clear view.

Standard Features

- Six high-intensity red digits (double-row discrete LED)
- Auto Learn mode of communication protocols
- Hold displayed weight (demand input)
- Software selectable standstill mode for no updates while in motion
- Mirror (reverse image) feature
- Durable weather-tight IP66 enclosure
- Adjustable daylight/night intensity
- Non-glare contrast filtered lens
- RS-232, 20 mA, and RS-485 communications
- Auto sensing 115/230 VAC power supply
- PEMs locations accommodate flange or VESA mounting brackets
- Polyethylene breather vent inhibits internal moisture buildup
- Red, green and arrow lights in Stop/Go model

Options

- Pole mount bracket
- Fiber-optic interface
- Radio interface

Specifications

Display:	6-digit, 7-segment discrete oval precision optical performance red LED lamps Contrast enhanced optical filtering lens 1- or 2- place decimal or comma indication 4 annunciators for GR, NT, lb, kg 4-inch red, green ball/arrow in Stop/Go model
Maximum Viewing Distance:	4-inch: 250 ft (75 m) 6-inch: 300 ft (100 m)
Input Interface:	RS-232, RS-485, 20 mA current loop (active or passive, switch selectable)
Output interface:	Independently configurable echo out port, RS-232 or 20 mA current loop (active or passive, switch selectable)
Input Data Format:	Baud Rate: 1200, 2400, 4800, 9600 and 19,200 self-learning or software selectable
Character Format:	7 or 8 data bits; even, odd, or no parity; 1 or 2 stop bits, self-learning or software selectable
Update:	Continuous or out-of-motion only; software selectable
Power Consumption:	4-inch: 21 watt 6-inch: 27 watt
Time:	Software enable/disable, 12- or 24-hour format
Date:	Software enable/disable, US or ISO format
Rating/Material:	IP66 Weather tight, mild steel, black powder coated
Dimensions:	4-inch (L x H): 22.28 in x 9.8 in 6-inch (L x H): 30.63 in x 12.77 in Stop/Go (L x H): 30.63 in x 12.77 in (flanges add 3.16 inches in width)
Weight:	4-inch: 20 lb (9 kg) 6-inch and Stop/Go: 25 lb (11 kg)
Operating Temperature Range:	-40°F to 120°F (-40°C to 49°C)
Warranty:	Two-year limited warranty

Your Rice Lake Weighing Systems distributor is:



2031 Reiser Ave. SE • New Philadelphia, OH 44663 • USA
TEL: 800-321-3396 • FAX: 800-99206679 • www.nascoop.com



An ISO registered company © 2016 Rice Lake Weighing Systems PN 168341 4/16
Specifications subject to change without notice.