

Summit® 3000

Low-Profile Floor Scale

Specifications

End Load Capacity:

- 100% full scale at 2,000 lb and 5,000 lb
- 80% full scale at 10,000 lb

Cable Length:

- 20 ft (6.1 m) (for connecting junction box to indicator)

Warranty:

- Summit 3000 weldment and load cells two years, all other components one year

Approvals:

- NTEP CC 92-001A9, Class III 5,000 d
- Measurement Canada AM-5530, Class III 5,000 d

Standard Features

- 4 NTEP Certified alloy steel shear-beam load cells
- Top access junction box
- Rugged diamond safety tread plate steel deck
- 4 adjustable rigid polyurethane rubber feet, 3 in (76.2 mm) diameter
- Signal trim summing board housed in ABS enclosure
- Threaded eyebolt hole (1/2–20NF) located in center of the deck for easy lifting
- 20 ft of EL147 load cell cable



APPROVALS



Measurement
Canada
Approved



The load cell cable exits weldment toward the interior of scale, allowing flexibility to route it out any side of scale to digital weight indicator.

Summit[®] 3000
Low-Profile Floor Scale

Part Number/Price

PART #	SIZE (W X L X H)	CAPACITY	EST. SHIP WEIGHT	PRICE
Single Scale				
74715	3 ft x 3 ft x 3.625 in	2,000 lb	190 lb	Consult
74716	4 ft x 4 ft x 3.625 in	2,000 lb	305 lb	Consult
74717	4 ft x 4 ft x 3.625 in	5,000 lb	305 lb	Consult
74718	4 ft x 4 ft x 3.625 in	10,000 lb	305 lb	Consult
74719	4 ft x 5 ft x 3.625 in	5,000 lb	395 lb	Consult
74720	4 ft x 5 ft x 3.625 in	10,000 lb	445 lb	Consult
74721	4 ft x 6 ft x 3.625 in	5,000 lb	470 lb	Consult
74722	4 ft x 6 ft x 3.625 in	10,000 lb	525 lb	Consult
74723	5 ft x 5 ft x 3.625 in	5,000 lb	505 lb	Consult
74724	5 ft x 5 ft x 3.625 in	10,000 lb	575 lb	Consult
Single Scale—Canadian Weights and Measures Certified				
77440	3 ft x 3 ft x 3.625 in	1,000 kg	190 lb	Consult
77373	4 ft x 4 ft x 3.625 in	1,000 kg	305 lb	Consult
77346	4 ft x 4 ft x 3.625 in	2,500 kg	305 lb	Consult
77347	4 ft x 4 ft x 3.625 in	5,000 kg	305 lb	Consult
82880	4 ft x 5 ft x 3.625 in	2,500 kg	395 lb	Consult
82881	4 ft x 5 ft x 3.625 in	5,000 kg	445 lb	Consult
77348	5 ft x 5 ft x 3.625 in	2,500 kg	505 lb	Consult
77349	5 ft x 5 ft x 3.625 in	5,000 kg	575 lb	Consult
5-Scale Package				
75809	3 ft x 3 ft x 3.625 in	2,000 lb	850 lb	Consult
75810	4 ft x 4 ft x 3.625 in	2,000 lb	1,400 lb	Consult
75811	4 ft x 4 ft x 3.625 in	5,000 lb	1,400 lb	Consult
75812	4 ft x 4 ft x 3.625 in	10,000 lb	1,400 lb	Consult
75813	4 ft x 5 ft x 3.625 in	5,000 lb	1,870 lb	Consult
75814	4 ft x 5 ft x 3.625 in	10,000 lb	2,115 lb	Consult
75815	4 ft x 6 ft x 3.625 in	5,000 lb	2,210 lb	Consult
75816	4 ft x 6 ft x 3.625 in	10,000 lb	2,495 lb	Consult
75817	5 ft x 5 ft x 3.625 in	5,000 lb	2,325 lb	Consult
75818	5 ft x 5 ft x 3.625 in	10,000 lb	2,675 lb	Consult
5-Scale—Canadian Weights and Measures Certified				
77472	3 ft x 3 ft x 3.625 in	1,000 kg	850 lb	Consult
77473	4 ft x 4 ft x 3.625 in	1,000 kg	1,400 lb	Consult
77474	4 ft x 4 ft x 3.625 in	2,500 kg	1,400 lb	Consult
77475	4 ft x 4 ft x 3.625 in	5,000 kg	1,400 lb	Consult
82885	4 ft x 5 ft x 3.625 in	2,500 kg	1,870 lb	Consult
82886	4 ft x 5 ft x 3.625 in	5,000 kg	2,115 lb	Consult
77476	5 ft x 5 ft x 3.625 in	2,500 kg	2,325 lb	Consult
77477	5 ft x 5 ft x 3.625 in	5,000 kg	2,675 lb	Consult

Options/Accessories

PART #	DESCRIPTION	EST. SHIP WEIGHT	PRICE
75819	Floor anchor plates, mild steel (set of 2)	—	Consult
Consult	Top access foot adjust holes	—	Consult



www.nascoop.com | Phone: 800-321-3396

480/480 Plus Legend™ Series

Digital Weight Indicator

Specifications

Power:

Line voltages: 90- 264 VAC
Frequency: 50 or 60 Hz

Power Consumption:

70mA at 115 VAC, 35 mA at 230 VAC with (10) 350Ω load cells

Excitation Voltage:

5VDC, 10 x 350Ω load cells

Analog Signal Input Range:

±7 mV/V

Analog Signal Sensitivity:

0.1 uV/graduation minimum,
0.5 uV/graduation recommended

Resolution:

Internal: 523,000 counts
Display: 100,000 graduations

Measurement Rate:

Selectable 5, 10, 20, 40 Hz

System Linearity:

Within 0.01% of full scale

Circuit Protection:

Immunity 10 V/m ESD ±10KV air ±6KV contact

RFI Protection:

Capacitor bypass and ESD suppressors

Serial Output:

Com 1: RS-232 full duplex
Com 2: RS-232 full duplex or 20 mA simplex, continuous
Both ports 1200, 2400, 4800, 9600, 19200, 38400 baud 7 or 8 data bits, even, odd or no parity

Display:

LED display, 0.8 in (20 mm), 6-digit, 7-segment

Status Annunciators:

Gross, net, center of zero, standstill, lb, kg, tare, preset tare

Keyboard:

Flat membrane panel, embossed keys, tactile feel

(Optional) Analog Output:

16-bit resolution, voltage output 0-10 VDC, current output 0-20 mA / 4-20 mA

(Optional) Relay Board:

2 opto-isolated, 5 to 24 VDC, active high inputs. 2 inputs (requires relay output option). Primary keys, pseudo functions, batching functions.
(4) 30 VDC, 2 amp dry-contact relays

(Optional) Ethernet and USB Board:

USB 5-pin header for PC, printer or flash drive. Ethernet TCP/IP, RJ45 jack, server and client ports.

Operating Temperature:

Legal: 14° F to 104° F (-10° C to 40° C)
Industrial: 14° F to 122° F (-10° C to 50° C)

Weight:

6.4 lb (2.9 kg)

Rating/Material:

Enclosure: NEMA Type 4X/IP66, heavy-gauge stainless steel

Warranty:

Two-year limited warranty

Approvals:

Measurement Canada AM-5892, Accuracy Class III/IIHD, 10,000d
NTEP CC 12-123, Accuracy Class III/IIIL, 10,000d
OIML R76/2006-NL1-12.48, T5692, TC8322 Accuracy Class III, 10,000d
CE Marked
C-UL pending



APPROVALS



Measurement
Canada
Approved




Standard Features

- LED display, 0.8 in (20 mm), 6-digit, 7-segment
- Time and date, battery backed
- Local/remote operation
- Numeric keypad (480 Plus)
- Keyed entries for tare and setpoint values (480 Plus)
- 2 independent serial ports
- NEMA Type 4X/IP66 stainless steel washdown enclosure
- Password protection for user and configuration changes
- Selectable conversion rate and display update rate
- Hardware or audit trail metrology sealing
- Programmable ticket formats for gross, net, accumulator and setpoints
- 5 continuous stream formats
- Adapter filter or rolling average filter
- Operator functions through menu for audit trail, preset tare, unit ID, accumulator, time and date, setpoints, communications and print formats
- 8 setpoints, sequenced batch engine
- Configurable with Revolution® software

Options

- Analog output, 0-10 VDC, 0-20 mA, 4-20 mA, selection for 20% offset
- Relay output, 2 digital inputs, four dry contact relays (supports 2 boards)
- Ethernet TCP/IP and USB interface (requires cable)
- Battery, rechargeable lithium ion
Power for 40 hours of battery life on one 350 ohm load
Power-saving modes for sleep and wake-up threshold



DIMENSIONS

A	9.50 in (241 mm)	E	2.75 in (70 mm)
B	10.00 in (254 mm)	F	7.00 in (177 mm)
C	11.00 in (279 mm)	G	6.00 in (152 mm)
D	3.65 in (92 mm)	H	3.75 in (95 mm)



480/480 Plus Legend Series

Digital Weight Indicator

Part Number/Price: 480

PART #	DESCRIPTION	EST. SHIP WEIGHT	PRICE
480 115 VAC †			
126564	480 LED	8 lb	Consult
130338	480 LED with analog output	8 lb	Consult
130340	480 LED with relay output	8 lb	Consult
480 90-264 VAC ††			
126565	480 LED	8 lb	Consult
130339	480 LED with analog output	8 lb	Consult
130341	480 LED with relay output	8 lb	Consult

Part Number/Price: 480 Plus

PART #	DESCRIPTION	EST. SHIP WEIGHT	PRICE
480 Plus 115 VAC †			
164588	480 Plus LED	8 lb	Consult
164589	480 Plus LED with analog output	8 lb	Consult
164590	480 Plus LED with relay output	8 lb	Consult
480 Plus 90-264 VAC ††			
164591	480 Plus LED	8 lb	Consult
164592	480 Plus LED with analog output	8 lb	Consult
164593	480 Plus LED with relay output	8 lb	Consult



†† CEE 7/7 plug
Euro plug



† NEMA Type 5-15 plug

Options/Accessories

PART #	DESCRIPTION	PRICE
131340	Mounting bracket for option boards	Consult
131341	Analog output, 0-10 VDC, 4-20 mA (requires 131340)	Consult
131342	Relay board, 2 digital inputs, 4 dry contact outputs (requires 131340)	Consult
164600	USB and Ethernet TCP/IP (requires 131340)	Consult
164604	Ethernet cable with cord grip, 6 ft	Consult
164602	USB cable with cord grip, type A female, 6 in	Consult
167707	USB cable with cord grip, type A male, 6 ft	Consult
167708	USB cable with cord grip, type B male, 6 ft	Consult
165379	Flash update cable	Consult
164650	Battery kit, rechargeable lithium ion	Consult
151100	A/D sealing kit, used with audit trail tracking	Consult
151099	Panel mount bezel (not NEMA rated)	Consult
83564	Clear protective overlay (package of five)	Consult
77925*	Revolution [®] scale software	Consult
119201	Installation manual	Consult
Primary Replacement Components		
131345	Overlay, 480 6-key, red window	Consult
159612	Overlay, 480 Plus with numeric keys, red window	Consult
131346	Display board, LED	Consult
131316	Power supply, 85-265 VAC	Consult
131318	CPU board	Consult
131319	A/D board	Consult

* Revolution can be downloaded for free at www.ricelake.com